SSM P/N CQJ04421

NOTES
1. MATERIALS:
   CERAMIC TO BE OPAQUE, 90-94% Al_2O_3
   SOLDER GLASS TO BE 7585.
   MIN. FILLBACK TO BE 0.25(.010)
   FROM CERAMIC EDGE.
   DIE ATTACH AREA TO BE R_a = .120
   MICROINCH MIN.
   LEAD FRAME TO BE ALLOY 42 OR
   EQUIVALENT WITH ALUMINUM
   BOND PADS, 100 MICROINCH THICK
   AND 35 MILS IN LENGTH WITH NO
   FILL BACK.
3. THERE WILL BE NO UNSUPPORTED
   BOND PADS GREATER THAN 0.25(.010)
4. ADJACENT BOND PADS MUST BE
   CO-PLANAR WITHIN 0.15(.006).
   TOTAL CO-PLANARITY NO GREATER
   THAN 0.25(.010)
5. THERE WILL BE NO NICKS, CUTS
   OR GLASS IN THE BOND PADS
   MINIMUM LATERAL METAL SEPARATION TO
   BE 0.20(.008)















JEDEC TYPE

OPEN DRW.

NAME			
44-D CLRD CERPAC J 44SD-4301			
SERIES	MATERIAL		
16 / 31	—		

KYOCERA CORPORATION KYOTO JAPAN

QC-044253-J-1